


FICHE TECHNIQUE CHAÎNE DROITE SOUDÉE "MAILLE LONGUE"

**Acier zingué
DIN 5685C**



Tolérance Ø fil $\pm 10\%$
Tolérance maillon $\pm 5\%$
Tolérance longueur 0 à $+ 10\%$

CODE	CODE EAN	LONGUEUR LIASSE (M)	d (mm) diamètre fil	L (mm) longueur maillon	l (mm) largeur maillon	CHARGE DE TRAVAIL (en kg)
995/2,5MMZ	3233690032809	25	2,5	29	11	30
995/3MMZ	3233690032823	25	3	32	12	55
995/3,5MMZ	3233690032847	25	3,5	35	13	75
995/4MMZ	3233690019688	25	4	40	16	100
995/4,5MMZ	3233690019664	25	4,5	42	17	125
995/5MMZ	3233690019701	25	5	44	19	165
995/6MMZ	3233690019725	25	6	52	24	225
995/7MMZ	3233690032861	25	7	61	28	300
995/8MMZ	3233690019749	12	8	66	32	400
995/10MMZ	3233690019640	10	10	83	40	620
995/12MMZ	3233690097457	10	12	100	50	900



Ne pas utiliser comme chaîne de levage industriel

