## SPECIFICATION PORTABLE AC

| | | |
|---|---|---|
| Product Pictures | |   |
| | | |
| model | | YAC-12CHPB/PD1(RZ) |
| Power supply (V-Ph-Hz) | | 220V~240V/50Hz |
| Water tank volume （L） | | 0,82 |
| Cooling Test Condition | | 35℃/24℃ |
| Cooling Capacity(W) | | 3500 |
| Cooling Capacity(Btu/h) | | 12000 |
| Cooling Input Power(W) | | 1345 |
| Cooling Input Current(A) | | 6,5 |
| EER(W/W) | | 2.6(A) |
| Suitable area(m2) | | 14-25㎡ |
| Heat pump / Elecment | | Heat pump |
| Heating Test Condition | | 21℃/12℃ |
| Heating Capacity(W) | | 3300 |
| Heating Capacity(Btu/h) | | 11200 |
| Heating Input Power(W) | | 1100 |
| Heating Input Current(A) | | 4,8 |
| COP(W/W) | | 3 |
| | | |
| Rated Power(W) | | 1550 |
| Rated Current(A) | | 7,9 |
| UL Rated Current (A) | | / |
| Indoor air flow(Hi/Med/Lo) (m3/h) | | 410/360/270 |
| Indoor air flow(Hi/Med/Lo)(CFM) | | 241/211/159 |
| Moisture Removal(L/h) Cooling | | 1,7 |
| Moisture Removal(L/day) Cooling | | 40,8 |
| Moisture Removal(pint/day) Cooling | | 86,1 |
| Sound (Hi/Med/Lo)(dB(A)) | | 52/49 |
| Sound Power | | 64 |
| Refrigerant type | | R290 |
| Refrigerant Charge (g) | | 210 |
| Refrigerant Charge (oz) | | 7,41 |
| Suction Pressure(Mpa) | | 1,2 |
| Discharge Pressure(Mpa) | | 2,3 |
| Suction Pressure(PSIG) | | 174 |
| Discharge Pressure(PSIG) | | 336 |
| | | |
| Compressor Model | | 44P273I |
| Type(Rotary, Reciprocating) | | Rotary |
| Brand | | RECHI |
| Packaging Information | | |
| Net weight (kg) | | 28,2 |
| Body demention (mm) | | 358*419*688 |
| Gross weight package (kg) | | 31,7 |
| Packing dimention (mm) | | 396*460*865 |
| Stuffing Quantity set(20'/40'/40'HQ) | | 140/300/444 |