

Série
849




DONNÉES
CAO
EN LIGNE



Écrous à sertir en aveugle ESM-R-KLSK

inox A2

tête affleurante | cylindrique cranté | ouvert



[1.4567]

M	$\frac{k}{l}$	l	N°	
M3	0,5 - 1,5	9,0	10849030200	500
D 5,0	k 0,4	dk 6,0	l₁ max. 7,0	↓ 3500 N
M4	0,5 - 3,0	10,0	10849040300	500
D 6,0	k 0,4	dk 7,0	l₁ max. 8,0	↓ 6500 N
M5	0,5 - 3,0	11,5	10849050300	500
	3,0 - 4,5	13,5	10849050450	500
D 7,0	k 0,5	dk 8,0	l₁ max. 8,5	↓ 10000 N
M6	0,5 - 3,0	14,0	10849060300	500
	3,0 - 5,0	16,0	10849060500	500
D 9,0	k 0,5	dk 10,0	l₁ max. 10,0	↓ 15000 N

M	$\frac{k}{l}$	l	N°	
M8	0,5 - 3,0	16,0	10849080300	500
	4,0 - 6,0	19,5	10849080600	500
D 11,0	k 0,5	dk 12,0	l₁ max. 11,5	↓ 25000 N
M10	1,0 - 3,5	19,2	10849100350	250
D 13,0	k 0,7	dk 14,0	l₁ max. 14,0	↓ 38000 N
M12	1,0 - 4,0	24,0	10849120400	100
D 16,0	k 0,7	dk 17,0	l₁ max. 16,0	↓ 50000 N