

- BRAVO is a fast assembly kit for single bottom-hinged window whose width does not exceed 1.5 m.
- Minimum space required: 20 mm from the vent upper profile.
- The conduit is supplied in 0.6 m bars, drown at one end: speed of assembly is ensured thanks to its insertion, with no need of joints.
- One bar of the conduit is already bended (50 mm radius), there is no need of any tool.
- Blister package for display in the shop, easy transport and storage guaranteed.
- Maximum opening: 250 mm; the kit is supplied complete with a pre-cut spent travel tube.
- For vents lower than 500 mm, reduce the stroke to 1/3 of the height by adjusting the end stroke spring, located by the control operator.

NOTE: to open more than one window, loose elements must be ordered (see pages 48-52).



⚠ The instructions for a safe installation are included in the section "SECURITY WARNINGS". On bottom hinged windows for safety reasons always install side checks.

PART No.

Conduit length		3,05 m	4,25 m	6,05 m
Colou	r White Black Grey	40649K 40652Y 40655E	40650U 40653 A 40656G	40651W 40654C 40657J
Items	contained in BRAVO			
Pos. 1 2 3 4 4A 5 6 7 8	Description Flat operator Locking opener Cable Conduit Bent conduit Saddle Lock spring Spent travel tube End plug	Q.ty 1 1 3,5 m 4 1 4 1	Q.ty 1 4,7 m 6 1 6 1	Q.ty 1 1 6,5 m 9 1 8 1

