

POSTES À SOUDER

SWX 180+ MMA





ÉCRAN LCD
Pour une configuration précise

Design léger et compact

Simple d'utilisation

Multifonction

+++

Synergique

Arc force

Compatible avec groupe électrogène

Hot Start

Convient pour le soudage avec électrodes rutiles, basiques et en acier inoxydable

Anti stick

FRÉQUENCE 50-60 HZ

ÉLECTRODES 1,6 Ø 4,0 Ø

PLAGE AMPERE 20-200A

MICRO PROCESSEUR


PINCE PORTE ÉLECTRODES


PINCE DE MASSE


BROSSE

INFORMATIONS D'EMBALLAGE

MODÈLE	SWX 180+ MMA
POIDS NET (KG)	4,4
DIMENSIONS (L X L X H / MM)	440 x 235 x 300



SWX 140 MMA



SWX 180+ MMA

INFORMATIONS TECHNIQUES

MODEL		SWX 140 MMA	SWX 180+ MMA
PART NUMBER		831120100	831120300
POWER VOLTAGE (V)		1 Phase AC 230 +/-15%	1 Phase AC 230 +/-15%
FREQUENCY (HZ)		50/60	50/60
NO-LOAD VOLTAGE (V)		60	62
OUPUT CURRENT (A)		20-140	20-200
DUTY CYCLE (A)	60 %	130	180
	100 %	108	140
ABSORPTION (KW)		3,79	5,41
FUSE (A)		16	16
INSULATION GRADE		F	F
IP RATE		21	21
COMPATIBLE WITH GENERATOR POWER		√	√
SYNERGY		NO	√
ARCFORCE		√	√ REGULABLE
HOT START		√	√ REGULABLE
ANTISTICKING		√	√
ACCESSORIES INCLUDED			
ELECTRODE HOLDER		√	√
EARTH CLAMP		√	√
BRUSH HAMMER		√	√

ÉLECTRODES

ÉPAISSEUR DES ÉLECTRODES mm	FE		FE		INOX	
	ÉLECTRODE RUTILE		ÉLECTRODE BASIQUE		ÉLECTRODE INOX	
	Ø mm	AMP	Ø mm	AMP	Ø mm	AMP
2-3 mm	1.6	20-40	-	-	-	-
2-5 mm	2.0	40-60	2.0	50-70	2.0	35-50
3-6 mm	2.5	60-90	2.5	70-90	2.5	50-80
4-8 mm	3.2	90-120	3.2	90-140	3.2	80-110
6-12 mm	4.0	120-160	4.0	140-190	4.0	110-190
7-14 mm	5.0	160-200	5.0	190-250	5.0	150-180

DIAMÈTRE DES ÉLECTRODES (MM)			
RUTILE	1,6-3,2	1,6-4,0	1,6-4,0
INOX	1,6-3,2	1,6-4,0	1,6-4,0
FONTE	1,6-3,2	1,6-4,0	1,6-4,0
BASIQUE	1,6-3,2	1,6-3,2	1,6-4,0
CELLULOSIQUE	-	-	-
ALUMINIUM	-	-	-